



# KMUX- 7440

## 4-port Multiplexer

The 4-port KMUX-7440 is a Multiplexer supports four access ports, two 1G SFP uplink ports and two 1G Ethernet ports. It is a 1RU high, 19" standard rack mountable unit. This 4-port Multiplexer can be co-located at the telecommunication service provider's Central Office or in a telecommunication room at a gated community and provides triple play broadband connectivity to the customers at its vicinity. This multiplexer can be managed locally or remotely through management interface ports.

### Technical Specifications:

#### Ethernet Uplink & Downlink Interfaces:

Downlink (Access) Ports	:	4 SFP ports
Uplink Ports	:	2 x SFP ports 2 x RJ45 Ethernet ports

#### Management Interface:

Management Port	:	1
Console Port	:	1

#### LED Indications:

LEDs	:	SYS, PWR, GE 1 & 2 & Access 1 - 4
------	---	-----------------------------------

#### Input Power:

Input	:	Single AC or Dual AC
Input Voltage	:	90 ~ 264VAC, 30W, 50/60 Hz

#### Weight and Dimension:

Weight	:	Approx. 3.10 Kgs.
Dimension (W x D x H)	:	442mm x 200mm x 44.45mm (1RU)



**THIS PAGE IS INTENTIONALLY LEFT BLANK**